

## CLAIMS

What is claimed is :

1. A method of simulating behavior of a flow interacting with an object, the method providing a simulated numerical representation in  $N$  dimensions,  $N \geq 3$ , that is  
5 composed of a plurality of approximated values at a multitude of points in at least a part of space where the flow interacts with the object, the approximated values being of a physical parameter  $u$  of the flow to which is associated a velocity field  $\vec{a}$  which determines a preferential direction, by means of a numerical scheme wherein at least one spatial  $p^{\text{th}}$  derivative  $D_p$ ,  $p \geq 1$ , of the parameter  $u$  is approximated  
10 at the points of the part of space, the method comprising the steps of :  
    using for the part of space a discrete  $N$ -dimensional grid constructed by  $N$  families of coordinate lines ;  
    computing, in at least one point  $P$  of the grid, called the point of computation, an approximated value  $D_p^A$  of  $D_p$  with an error  $\epsilon_n$ , by using values  $u_s$  of the  
15 parameter in a collection of grid points, called the stencil  $S$ , and computational functions, evaluated with the values  $u_s$ , the computational functions depending on the numerical framework in which  $D_p$  is expressed,  
    choosing the computational functions for the approximated value  $D_p^A$  in such a way that the approximated value  $D_p^A$  is optimized for the preferential direction,  
20 and  
    wherein the stencil  $S$  contains at least one point situated outside all the coordinate lines passing through the point of computation  $P$ , and the stencil  $S$  contains at least a first point and a second point, the first point being defined by  $N$  first coordinate lines of the  $N$  families of lines, the second point being defined  
25 by  $N$  second coordinate lines of the  $N$  families of lines, and for at least one family  $N_f$  of the coordinate lines, the first coordinate line belonging to the family  $N_f$  is different from and not adjacent to the second coordinate line belonging to the same family  $N_f$  ; and  
    outputting the numerical representation that simulates, for the part of space,  
30 behavior of the flow interacting with the object.
2. The method of claim 1, wherein for varying preferential directions, the approximation  $D_p^A$  depends continuously on the values  $u_s$ .

3. The method of claim 1, wherein the computing step of  $D_p^A$  comprises the steps of :
  - providing a local basis  $B(\vec{e}_1, \vec{e}_2, \vec{e}_3, \dots)$  of curvilinear coordinates which has the unit vector  $\vec{e}_1$  along the preferential direction, and
  - choosing the computational functions so that a contribution to the error  $\epsilon_n$  of at least one pure or one mixed derivative as expressed in the local basis  $B$  is minimized, while using as a formulation of the values  $u_s$  of the parameter at each of the points of the stencil  $S$ , a truncated Taylor series expansion with respect to the point of computation  $P$  with an error, called the truncation error  $\epsilon_s$ .
4. The method of claim 3, wherein the computational functions are individual coefficients  $C_s$  and the approximated value  $D_p^A$  is a linear combination of values  $u_s$  of the parameter.
5. The method of claim 3, wherein the computing step of  $D_p^A$  comprises the steps of :
  - using an integral formulation for the computation of the derivative  $D_p$  with computational functions which are fluxes through a control volume,
  - computing in at least one volume an approximated value  $D_p^A$  of  $D_p$  with an error  $\epsilon_n$ , where the approximated value is a function of the flux formulation employed.
6. The method of claim 3, wherein the computing step of  $D_p^A$  comprises the steps of :
  - subdividing the part of space into elements, containing nodes at which the approximation of the physical parameter  $u$  is stored,
  - defining basis computational functions  $\phi$ , called interpolation functions, on the elements, where the interpolation functions are used to approximate the physical value  $u$  on the element,
  - computing the integral of the derivative  $D_p$  on the element, using a test computational function  $\psi$ , called weighting function,
  - computing in at least one element an approximated value  $D_p^{\phi, \psi}$  of  $D_p$  with an error  $\epsilon_n$ , where the approximated value is a function of the interpolation functions  $\phi$  and the weighting function  $\psi$ .
7. The method of claim 3, wherein the computing step of  $D_p^A$  comprises the steps of :
  - subdividing the part of space into elements, containing nodes at which the approximation of the physical parameter  $u$  is stored,

defining basis computational functions  $\phi$ , called interpolation functions, on the elements, where the interpolation functions are used to approximate the physical value  $u$  on the element,

5        computing the integral  $I_{el}$  of the derivative  $D_p$  on volumes, and distributing parts  $\alpha_i I_{el}$  to nodes  $i$ , where  $\alpha_i$  represent computational functions called distribution coefficients.

8. The method of claim 3, wherein the computing step of  $D_p^A$  comprises the steps of :  
       subdividing the part of space into elements, containing nodes at which the approximation of the physical parameter  $u$  is stored,

10        defining basis computational functions  $\phi$ , called interpolation functions, on the elements, where the interpolation functions are used to approximate the physical value  $u$  on the element,

      computing fluxes  $f$  at the surfaces of volumes, and distributing parts  $\alpha_i f$  to nodes  $i$ , where  $\alpha_i$  represent computational functions called distribution coefficients,

15        9. The method of claim 1, wherein the computing step of  $D_p^A$  comprises the steps of :  
       using a representation of the numerical solutions in Fourier components, and  
       choosing in the approximated value  $D_p^A$  the computational functions in such a way that the Fourier components are optimized for certain directions which are related to the velocity  $\vec{a}$ , while using the values  $u_s$  of the parameter at each of the  
 20        points of the stencil  $S$  in the Fourier representation.

10. The method of claim 9, wherein the computational functions are individual coefficients  $C_s$  and the approximated value  $D_p^A$  is a linear combination of values  $u_s$  of the parameter.

11. The method of claim 9, wherein the computing step of  $D_p^A$  comprises the steps of :  
 25        using an integral formulation for the computation of the derivative  $D_p$  with computational functions which are fluxes through a control volume,  
       computing in at least one volume an approximated value  $D_p^A$  of  $D_p$  with an error  $\epsilon_n$ , where the approximated value is a function of the flux formulation employed.

30        12. The method of claim 9, wherein the computing step of  $D_p^A$  comprises the steps of :  
       subdividing the part of space into elements, containing nodes at which the approximation of the physical parameter  $u$  is stored,

defining basis computational functions  $\phi$ , called interpolation functions, on the elements, where the interpolation functions are used to approximate the physical value  $u$  on the element,

5        computing the integral of the derivative  $D_p$  on the element, using a test computational function  $\psi$ , called weighting function,

      computing in at least one element an approximated value  $D_p^{\phi,\psi}$  of  $D_p$  with an error  $\epsilon_n$ , where the approximated value is a function of the interpolation functions  $\phi$  and the weighting function  $\psi$ .

13. The method of claim 9, wherein the computing step of  $D_p^A$  comprises the steps of :  
10        subdividing the part of space into elements, containing nodes at which the approximation of the physical parameter  $u$  is stored,

      defining basis computational functions  $\phi$ , called interpolation functions, on the elements, where the interpolation functions are used to approximate the physical value  $u$  on the element,

15        computing the integral  $I_{el}$  of the derivative  $D_p$  on volumes, and distributing parts  $\alpha_i I_{el}$  to nodes  $i$ , where  $\alpha_i$  represent computational functions called distribution coefficients.

14. The method of claim 9, wherein the computing step of  $D_p^A$  comprises the steps of :  
20        subdividing the part of space into elements, containing nodes at which the approximation of the physical parameter  $u$  is stored,

      defining basis computational functions  $\phi$ , called interpolation functions, on the elements, where the interpolation functions are used to approximate the physical value  $u$  on the element,

25        computing fluxes  $f$  at the surfaces of volumes, and distributing parts  $\alpha_i f$  to nodes  $i$ , where  $\alpha_i$  represent computational functions called distribution coefficients,

15. The method of claim 1, wherein the  $N$ -dimensional grid is expressed in a coordinate system which is chosen from the group consisting of : rectangular coordinates, spherical coordinates, cylindrical coordinates, parabolic cylindrical coordinates, paraboloidal coordinates, elliptic cylindrical coordinates, prolate spheroidal coordinates, oblate spheroidal coordinates, bipolar coordinates, toroidal coordinates, conical coordinates, confocal ellipsoidal coordinates and confocal paraboloidal coordinates.  
30

16. The method of claim 1, wherein the  $N$ -dimensional grid is chosen from the group consisting of : a grid with non-uniform mesh spacing, a grid which is moving, a

grid which is deforming, a grid which is rotating, and a grid which is staggered, and any combination thereof.

17. The method of claim 1, wherein the spatial  $p^{\text{th}}$  derivative  $D_p$  is a pure derivative  $\partial^p u / \partial e_i^p$ .
- 5 18. The method of claim 1, wherein  $p = 1$ .
19. The method of claim 1, wherein  $p = 2$ .
20. The method of claim 1, wherein the spatial  $p^{\text{th}}$  derivative  $D_p$  is a mixed derivative  $\partial^p u / \partial e_1^{p_1} \partial e_2^{p_2} \dots$  with  $p_1 + p_2 + \dots = p$ .
21. The method of claim 3, computing an approximated value  $D_1^A$  of  $D_1$ , where the  
10 approximated value is denoted by

$$\begin{pmatrix} (u_x)_{i,j,k,\dots} \\ (u_y)_{i,j,k,\dots} \\ (u_z)_{i,j,k,\dots} \\ \vdots \end{pmatrix}, \quad (27)$$

wherein

$$\begin{aligned} (u_x)_{i,j,k,\dots} &= \frac{1}{\Delta x} \left\{ a_{-m} u_{i-m,j,k,\dots} + a_{-m+1} u_{i-m+1,j,k,\dots} + \dots \right. \\ &\quad \left. + a_{n-1} u_{i+n-1,j,k,\dots} + a_n u_{i+n,j,k,\dots} + Tx \right\}, \\ 15 \quad (u_y)_{i,j,k,\dots} &= \frac{1}{\Delta y} \left\{ a_{-m} (u_{i-m,j-m,k,\dots} - u_{i-m,j,k,\dots}) \right. \\ &\quad \left. + a_{-m+1} (u_{i-m+1,j-m+1,k,\dots} - u_{i-m+1,j,k,\dots}) + \dots \right. \\ &\quad \left. + a_{n-1} (u_{i+n-1,j+n-1,k,\dots} - u_{i+n-1,j,k,\dots}) \right. \\ &\quad \left. + a_n (u_{i+n,j+n,k,\dots} - u_{i+n,j,k,\dots}) + Ty \right\}, \\ 20 \quad (u_z)_{i,j,k,\dots} &= \frac{1}{\Delta z} \left\{ a_{-m} (u_{i-m,j-m,k-m,\dots} - u_{i-m,j-m,k,\dots}) \right. \\ &\quad \left. + a_{-m+1} (u_{i-m+1,j-m+1,k-m+1,\dots} - u_{i-m+1,j-m+1,k,\dots}) + \dots \right. \\ &\quad \left. + a_{n-1} (u_{i+n-1,j+n-1,k+n-1,\dots} - u_{i+n-1,j+n-1,k,\dots}) \right. \\ &\quad \left. + a_n (u_{i+n,j+n,k+n,\dots} - u_{i+n,j+n,k,\dots}) + Tz \right\}, \\ &\vdots \end{aligned} \quad (28)$$

wherein  $a_{-m} \neq 0$ ,  $a_n \neq 0$ ,  $m$  and  $n$  are given integers,  $m + n > 0$ , and  $m + n >$   
25  $1$  if  $m * n = 0$ , the terms  $Tx$ ,  $Ty$ ,  $Tz$ ,  $\dots$  represent the degrees of freedom which are used in the optimization of the approximated value  $D_1^A$ , and where indices  $(i, j, k, \dots)$  define the point of computation  $P$  on the  $N$ -dimensional grid,

and  $\Delta x, \Delta y, \Delta z, \dots$  denote the mesh spacings of the  $N$ -dimensional grid in each coordinate direction.

22. The method of claim 21, computing an approximated value  $D_1^A$  of  $D_1 = \partial u / \partial e_1$  by a discretization of order  $M$ , in which the terms  $\partial^{M+1} u / \partial e_2^{M_2} \partial e_3^{M_3} \dots$  with  $M_2 + M_3 + \dots = M + 1$  are eliminated in the approximated value  $D_1^A$ .
23. The method of claim 21, computing an approximated value  $D_1^A$  of  $D_1 = \partial u / \partial e_1$  by a discretization of order  $M$ , in which the terms  $\partial^{M+1} u / \partial e_1^{M_1} \partial e_2^{M_2} \partial e_3^{M_3} \dots$  with  $M_1 + M_2 + M_3 + \dots = M + 1$  and  $M_1 < M + 1$  are eliminated in the approximated value  $D_1^A$  in the case that  $\vec{e}_1$  is along the  $x$ -axis or along diagonals.
24. The method of claim 1, computing an approximated value  $D_1^A$  of  $D_1$ , where the approximated value is denoted by

$$\begin{pmatrix} (u_x)_{i,j,k,\dots} \\ (u_y)_{i,j,k,\dots} \\ (u_z)_{i,j,k,\dots} \\ \vdots \end{pmatrix}, \quad (29)$$

wherein

$$\begin{aligned} (u_x)_{i,j,k,\dots} &= \frac{1}{\Delta x} \left\{ a_{-m} u_{i-m,j,k,\dots} + a_{-m+1} u_{i-m+1,j,k,\dots} + \dots \right. \\ &\quad \left. + a_{n-1} u_{i+n-1,j,k,\dots} + a_n u_{i+n,j,k,\dots} \right\}, \\ (u_y)_{i,j,k,\dots} &= \frac{1}{\Delta y} \left\{ a_{-m} (u_{i-m,j-m,k,\dots} - u_{i-m,j,k,\dots}) \right. \\ &\quad + a_{-m+1} (u_{i-m+1,j-m+1,k,\dots} - u_{i-m+1,j,k,\dots}) + \dots \\ &\quad + a_{n-1} (u_{i+n-1,j+n-1,k,\dots} - u_{i+n-1,j,k,\dots}) \\ &\quad \left. + a_n (u_{i+n,j+n,k,\dots} - u_{i+n,j,k,\dots}) \right\}, \\ (u_z)_{i,j,k,\dots} &= \frac{1}{\Delta z} \left\{ a_{-m} (u_{i-m,j-m,k-m,\dots} - u_{i-m,j-m,k,\dots}) \right. \\ &\quad + a_{-m+1} (u_{i-m+1,j-m+1,k-m+1,\dots} - u_{i-m+1,j-m+1,k,\dots}) + \dots \\ &\quad + a_{n-1} (u_{i+n-1,j+n-1,k+n-1,\dots} - u_{i+n-1,j+n-1,k,\dots}) \\ &\quad \left. + a_n (u_{i+n,j+n,k+n,\dots} - u_{i+n,j+n,k,\dots}) \right\}, \\ &\vdots \end{aligned} \quad (30)$$

- wherein  $a_{-m} \neq 0$ ,  $a_n \neq 0$ ,  $m$  and  $n$  are given integers,  $m + n > 0$ , and  $m + n > 1$  if  $m * n = 0$ , and where indices  $(i, j, k, \dots)$  define the point of computation  $P$  on the  $N$ -dimensional grid, and  $\Delta x, \Delta y, \Delta z, \dots$  denote the mesh spacings of the  $N$ -dimensional grid in each coordinate direction.

25. The method of claim 21, wherein

$$\begin{aligned}
 (u_x)_{i,j,k,\dots} &= \frac{1}{\Delta x} \left\{ \frac{1}{2} (u_{i+1,j,k,\dots} - u_{i-1,j,k,\dots}) + Tx \right\} , \\
 (u_y)_{i,j,k,\dots} &= \frac{1}{\Delta y} \left\{ \frac{1}{2} (u_{i+1,j+1,k,\dots} - u_{i+1,j,k,\dots} + u_{i-1,j,k,\dots} - u_{i-1,j-1,k,\dots}) + Ty \right\} , \\
 (u_z)_{i,j,k,\dots} &= \frac{1}{\Delta z} \left\{ \frac{1}{2} (u_{i+1,j+1,k+1,\dots} - u_{i+1,j+1,k,\dots} \right. \\
 &\quad \left. + u_{i-1,j-1,k,\dots} - u_{i-1,j-1,k-1,\dots}) + Tz \right\} , \\
 &\vdots
 \end{aligned} \tag{31}$$

26. The method of claim 21, wherein

$$\begin{aligned}
 (u_x)_{i,j,k,\dots} &= \frac{1}{\Delta x} \left\{ \frac{1}{12} (u_{i-2,j,k,\dots} - 8u_{i-1,j,k,\dots} + 8u_{i+1,j,k,\dots} - u_{i+2,j,k,\dots}) + Tx \right\} , \\
 (u_y)_{i,j,k,\dots} &= \frac{1}{\Delta y} \left\{ \frac{1}{12} (u_{i-2,j-2,k,\dots} - u_{i-2,j,k,\dots} \right. \\
 &\quad - 8u_{i-1,j-1,k,\dots} + 8u_{i-1,j,k,\dots} \\
 &\quad + 8u_{i+1,j+1,k,\dots} - 8u_{i+1,j,k,\dots} \\
 &\quad \left. - u_{i+2,j+2,k,\dots} + u_{i+2,j,k,\dots}) + Ty \right\} , \\
 (u_z)_{i,j,k,\dots} &= \frac{1}{\Delta z} \left\{ \frac{1}{12} (u_{i-2,j-2,k-2,\dots} - u_{i-2,j-2,k,\dots} \right. \\
 &\quad - 8u_{i-1,j-1,k-1,\dots} + 8u_{i-1,j-1,k,\dots} \\
 &\quad + 8u_{i+1,j+1,k+1,\dots} - 8u_{i+1,j+1,k,\dots} \\
 &\quad \left. - u_{i+2,j+2,k+2,\dots} + u_{i+2,j+2,k,\dots}) + Tz \right\} , \\
 &\vdots
 \end{aligned} \tag{32}$$

27. The method of claim 21, wherein

$$\begin{aligned}
 (u_x)_{i,j,k,\dots} &= \frac{1}{\Delta x} \left( \frac{3}{2} u_{i,j,k,\dots} - 2u_{i-1,j,k,\dots} + \frac{1}{2} u_{i-2,j,k,\dots} + Tx \right) , \\
 (u_y)_{i,j,k,\dots} &= \frac{1}{\Delta y} \left( -2(u_{i-1,j-1,k,\dots} - u_{i-1,j,k,\dots}) \right. \\
 &\quad \left. + \frac{1}{2} (u_{i-2,j-2,k,\dots} - u_{i-2,j,k,\dots}) + Ty \right) , \\
 (u_z)_{i,j,k,\dots} &= \frac{1}{\Delta z} \left( -2(u_{i-1,j-1,k-1,\dots} - u_{i-1,j-1,k,\dots}) \right. \\
 &\quad \left. + \frac{1}{2} (u_{i-2,j-2,k-2,\dots} - u_{i-2,j-2,k,\dots}) + Tz \right) , \\
 &\vdots
 \end{aligned} \tag{33}$$

28. A simulation method according to claim 1, in three dimensions, obtaining the approximation  $D_p^A$  with order  $M$  of the derivative  $D_p = \partial^p u / \partial e_1^{p_1} \partial e_2^{p_2} \partial e_3^{p_3}$  with  $p_1 + p_2 + p_3 = p$  on a grid of given extent from the output of the program generate-discretizations which is given in appendices 1-5.
29. A simulation method according to claim 28, wherein the input parameter optimize has the value 1 or 2.
30. A simulation method according to claim 28, wherein the input parameter order has the value 1.
31. The method of claim 3, computing in three dimensions an approximation of the second derivative  $D_2 = \partial^2 u / \partial e_1^2$ , where the approximation  $D_2^A$  is expressed in the terms  $u_{xx}$ ,  $u_{yy}$ ,  $u_{zz}$ ,  $u_{xy}$ ,  $u_{yz}$  and  $u_{zx}$  which are given by

$$\begin{aligned}
 (u_{xx})_{i,j,k} &= \frac{1}{(\Delta x)^2} (u_{i+1,j,k} - 2u_{i,j,k} + u_{i-1,j,k} + Txx) , \\
 (u_{yy})_{i,j,k} &= \frac{1}{(\Delta y)^2} (u_{i,j+1,k} - 2u_{i,j,k} + u_{i,j-1,k} + Tyy) , \\
 (u_{zz})_{i,j,k} &= \frac{1}{(\Delta z)^2} (u_{i,j,k+1} - 2u_{i,j,k} + u_{i,j,k-1} + Tzz) , \\
 (u_{xy})_{i,j,k} &= \frac{1}{\Delta x \Delta y} \left\{ \frac{1}{2} (u_{i+1,j+1,k} - u_{i,j+1,k} - u_{i+1,j,k} + 2u_{i,j,k} \right. \\
 &\quad \left. - u_{i-1,j,k} - u_{i,j-1,k} + u_{i-1,j-1,k}) + Txy \right\} , \\
 (u_{yz})_{i,j,k} &= \frac{1}{\Delta y \Delta z} \left\{ \frac{1}{4} (u_{i+1,j+1,k+1} - u_{i+1,j,k+1} - u_{i+1,j+1,k} + u_{i+1,j,k} + \right. \\
 &\quad u_{i,j+1,k+1} - u_{i,j,k+1} - u_{i,j+1,k} + 2u_{i,j,k} \\
 &\quad - u_{i,j-1,k} - u_{i,j,k-1} + u_{i,j-1,k-1} + \\
 &\quad \left. u_{i-1,j-1,k-1} - u_{i-1,j-1,k} - u_{i-1,j,k-1} + u_{i-1,j,k}) + Tyz \right\} , \\
 (u_{zx})_{i,j,k} &= \frac{1}{\Delta z \Delta x} \left\{ \frac{1}{4} (u_{i+1,j+1,k+1} - u_{i,j+1,k+1} - u_{i+1,j+1,k} + u_{i,j+1,k} + \right. \\
 &\quad u_{i+1,j,k+1} - u_{i+1,j,k} - u_{i,j,k+1} + 2u_{i,j,k} \\
 &\quad - u_{i-1,j,k} - u_{i,j,k-1} + u_{i-1,j,k-1} + \\
 &\quad \left. u_{i-1,j-1,k-1} - u_{i-1,j-1,k} - u_{i,j-1,k-1} + u_{i,j-1,k}) + Tzx \right\} \quad (34)
 \end{aligned}$$

wherein the terms  $Txx$ ,  $Txy$ ,  $Txz$ ,  $Tyy$ ,  $Tyz$  and  $Tzz$  represent the degrees of freedom which are used in the optimization of the approximated value  $D_2^A$ , and where indices  $(i, j, k)$  define the point of computation  $P$  on the three-dimensional grid, and  $\Delta x, \Delta y, \Delta z$  denote the mesh spacings of the three-dimensional grid in each coordinate direction.

32. The method of claim 1, wherein  $D_p^A = \sum_n L_n D_{p,n}^A$  where  $L_n$  are constants and each  $D_{p,n}^A$  is a function of values  $u_s$  of the parameter in a collection of grid points, called



stencil  $S_n$ , with individual computation functions, which depend on the numerical framework in which  $D_{p,n}^A$  is expressed, and wherein in the approximation  $D_{p,n}^A$ , the computation functions are chosen in such a way that the approximated value  $D_{p,n}^A$  is optimized for the preferential direction.

- 5     33. The method of claim 1, wherein  $D_p^A = \sum_n L_n D_{p,n}^A$  where  $L_n$  are limiting functions of the values  $u_s$  of the stencil  $S$ , and at least one  $D_{p,n}^A$  is a function of values  $u_s$  of the parameter in a collection of grid points, called stencil  $S_n$ , with individual computation functions, which depend on the numerical framework in which  $D_{p,n}^A$  is expressed, and wherein in the approximation  $D_{p,n}^A$ , the computation functions  
10     are chosen in such a way that said approximated value  $D_{p,n}^A$  is optimized for the preferential direction.
34. The method of claim 1, wherein the stencil  $S$  is chosen from the group consisting of : upwind discretization stencils, centered discretization stencils, and discretiza-  
15     tion stencils which are a combination of at least one upwind discretization stencil and at least one centered discretization stencil.
35. The method of claim 1, wherein the numerical discretization is a non-linear discretization.
36. The method of claim 1, wherein the numerical scheme is chosen from the group consisting of : the Lax-Wendroff scheme, the Lax-Friedrich scheme, the MacCor-  
20     mack scheme, the leap-frog scheme, the Crank-Nicholson scheme, the Stone-Brian scheme, the box scheme, Henn's scheme, the QUICK scheme, the  $\kappa$  scheme, the Flux Corrected Transport (FTC) scheme, the family of ENO schemes, schemes in the class of the Piecewise Parabolic Method (PPM), multi-level schemes, and schemes obtained with the fractional step method and variants thereof.
- 25     37. The method of claim 1, wherein the numerical scheme includes the discretization of a plurality of equations.
38. The method of claim 1 for the numerical simulation of physical phenomena which are modeled by the Navier-Stokes equations with equation(s) of state.
39. The method of claim 1 for the numerical simulation of physical phenomena which  
30     are modeled by the Euler equations with equation(s) of state.
40. The method of claim 1 for the numerical simulation of physical phenomena which are modeled by the magneto-hydrodynamic equations with equation(s) of state.

41. The method of claim 1 in combination with at least one model for the physical phenomena chosen from the group consisting of : equations to model turbulence, equations to model chemical reactions, equations to model electromagnetic phenomena, equations to model multiphase flow and equations to model multi-physics phenomena.
42. The method of claim 1 for the numerical simulation of physical phenomena in combination with at least one acceleration technique chosen from the group consisting of : local time-stepping, multi-grid, GMRES and preconditioning.
43. The method of claim 1 for the simulation of a physical phenomenon which includes a material flow.
44. The method of claim 1 for the simulation of a physical phenomenon which includes a material object interacting with material flow.
45. The method of claim 1 for the simulation of a physical phenomenon which includes a vehicle.
46. The method of claim 1 for the simulation of a physical phenomenon which includes a rotating blade.
47. The method of claim 1 for the simulation of at least a part of the atmosphere of the earth.
48. The method of claim 1 for the numerical simulation of oil recovery.
49. The method of claim 1 for the numerical simulation of physical phenomena which include combustion.
50. A data processing system programmed to implement a simulation method according to claim 1.
51. A computer program that can be loaded in a data processing system so as to implement a method according to claim 1.
52. A digital storage computer-readable medium containing a stored computer program that is configured to be loadable in a data processing system so as to implement a method according to claim 1.